

TEC

TOSHIBA TEC On-Site Color Printer

CB-416-T3-QQ/QP

Key Operation Specification

First Edition: September 14, 1998
Second Edition: February 22, 2000

TOSHIBA TEC CORPORATION

TABLE OF CONTENTS

	Page
1. SCOPE	1
2. OUTLINE.....	1
3. DIP SWITCH FUNCTIONS	2
4. OPERATION PANEL	4
5. ONLINE MODE	4
5.1 KEY FUNCTION.....	4
5.2 LED FUNCTION.....	4
5.3 LCD FUNCTION	5
5.4 ONLINE MODE OPERATION EXAMPLE.....	5
5.5 RESET	6
5.6 LCD MESSAGES AND LED INDICATIONS	7
5.7 LCD MESSAGES IN DIFFERENT LANGUAGES.....	9
6. SYSTEM MODE.....	10
6.1 OUTLINE OF SYSTEM MODE	10
6.2 SELF TEST	11
6.2.1 Self Test Operation Example.....	11
6.2.2 Self Test Items.....	13
6.2.3 Self Test Results Print Samples	15
6.2.4 Self Test Print Contents.....	16
6.3 VARIOUS PARAMETERS SETTING.....	22
6.3.1 Various Parameters Setting Example.....	22
6.3.2 Print Density Fine Adjustment Setting Example	23
6.3.3 X/Y Direction Fine Adjustment Setting Example	24
6.3.4 Printer Parameters Setting Example	31
6.3.5 Setting Contents	32
6.4 TEST PRINT	42
6.4.1 Test Print Operation Example	42
6.4.2 Setting Contents	46
6.4.3 Test Print Samples	50
6.5 RAM CLEAR	52
6.5.1 RAM Clear Operation Example	52
6.5.2 RAM Clear Contents	53

1. SCOPE

This specification applies to the key operations using the keys and the display panel of CB-416-T3-QQ/QP on-site color printers.

2. OUTLINE

Keyboard operations are roughly classified into the online mode in which a pause/restart is carried out and error messages are displayed, and the system mode in which the self-test and the setting of various parameters are performed.

This specification describes the key operation procedures using the printer keys and the display panel.

[Click here to download the full manual at THE-CHECKOUT-TECH.COM](#)